

ColorScape® WS-1

Wet Side Surface Treatment for Dry Cast Pavers & Slabs

Features and Benefits

- ColorScape WS-1 is applied inline on the wet side during the manufacturing process, and is cured into the paver surface.
- Deeper, richer color hues especially reds and charcoals.
- Sustained color fastness over time.
- Improves resistance to acid rain.
- Resistant to light and moderate abrasion from foot traffic.
- Applied inline during manufacturing process to assure quality application. Protection is in place before the pavers reach the jobsite.
- Easy to apply, does not require major changes to production
- Natural matte appearance

Guidelines for Use

Application Rate: ColorScape WS-1 coverage rate will vary depending on the quality of the paver surface and the desired benefits.

- Optimal coverage range for through mix pavers is 150 g/m² to 200 g/m².
- Optimal coverage range for face mix pavers is 100 g/m² to 150 g/m².

Due to variations in local materials, paver absorption and project requirements, coverage rates outside the recommended range may be required. Please consult with your Technical Services Representative for more information.

Recommended Application Method: ColorScape WS-1 is applied inline on the wet side with specialized equipment during the paver manufacturing process.



Description

ColorScape WS-1 applied inline on the wet side during paver manufacture. It is a component of the ColorScape® EverBold® System to improve the optical properties of concrete pavers with deeper, richer color hues and improved color fastness.

Recommended For

Dry Cast Pavers & Slabs

Technical Information

Color: Opaque White

Health & Safety

Consult SDS for Safety Information



ColorScape® WS-1

Wet Side Surface Treatment for Dry Cast Pavers & Slabs

Product Storage and Shelf Life

Freeze Protection: ColorScape WS-1 must be protected from freezing.

Do not store at temperatures below 40°F (5°C). The admixture is not usable after it has frozen.

Protect from Direct Sunlight: ColorScape WS-1 must be protected from direct sunlight. DO NOT store where container is exposed to direct sunlight.

Shelf life: One year in original unopened container.

Contact

ACM Chemistries, Inc.

P.O. Box 920430 Norcross, GA 30010

770-417-3490

acmchem.com

