

# BoardShield™

Protects and Keeps Boards and Pallets Clean

## Features and Benefits

- Highly effective means to keep boards clean and extend board life.
- Regular use reduces buildup of concrete residue and other materials, including overspray from paver surface treatments.
- Blend of special lubricants designed to reduce adhesion to board surfaces, makes boards easier to clean and keep them clean. Will not stain concrete when used as recommended.
- Penetrates and conditions the surfaces of metal and composite boards with each application.
- Reduces concrete unit adhesion to pallets that can cause difficulty in de-palletizing operations. For example: large format, wet cast slabs may be easier to depallet when adhesion between concrete unit and pallet is reduced.

## Guidelines for Use

Apply with dedicated board spray unit on the wet side or dry side.  
Apply to all production boards (both sides) initially. Continue regular application until boards are conditioned, then apply as needed.  
Apply to the entire board surface for best results.  
Recommended application rate of approximately 20 g / board surface.  
May require higher application during initial use.  
Must be used in conjunction with a board scraper to be fully effective.  
Do not use when ambient temperature is below freezing (32 °F or 0 °C).

## Product Storage and Shelf Life

**Circulation Required:** Continuous mechanical stirring or recirculation pumping is recommended to maintain homogeneity and ensure product performance. Your local Technical Services Representative will assist you in this process. Do not use pressurized air for agitation.

## Description

BoardShield works to reduce residue buildup, and make it easier to clean boards and pallets used in the manufacture of concrete products.

## Recommended For

Keeping boards clean

## Packaging

5 gallon Pails  
55 gallon Drums  
265 gallon Totes

## Technical Information

Color: White

## Health & Safety

Consult SDS for Safety Information



# BoardShield™

## Protects and Keeps Boards and Pallets Clean

---

BoardShield has low volatility and is non-flammable. However, **always store below 140° F (60° C)**. BoardShield (like most lubricants) can be combustible when exposed to spark or flames.

**Protect from Direct Sunlight:** BoardShield must be protected from direct sunlight. DO NOT store where container is exposed to direct sunlight.

**Freeze Protection:** BoardShield must be protected from freezing. Do not store at temperatures below 40° F (5° C). The product is not usable after it has frozen.

**Shelf life:** One year in original unopened container.

### Contact

ACM Chemistries, Inc.

P.O. Box 920430 Norcross, GA 30010 770-417-3490 [acmchem.com](http://acmchem.com)

