

ProClean™

Metal Cleaner and Conditioner for Concrete Mixers

Features and Benefits

- Regular use will noticeably reduce the time and effort required to clean concrete mixers
- Blend of special lubricants that are designed to reduce the adhesion of fresh concrete to metal parts
- Penetrates and conditions metal surfaces with each application

Guidelines for Use

Apply with low pressure sprayer. After cleaning the mixer and machinery at the end of the day, apply a light coating of ProClean to all metal surfaces that will be in contact with fresh concrete. Repeat at the end of every day. With regular use, ease of cleaning will improve. Do not use when ambient temperature is below freezing (32°F or 0°C).

Product Storage and Shelf Life

ProClean has low volatility and is non-flammable. However, **always store below 140°F (60°C)**. ProClean (like most lubricants) can be combustible when exposed to spark or flames.

Freeze Protection: ProClean must be protected from freezing. Do not store at temperatures below 40° F (5° C). The cleaner is not usable after it has frozen.

Protection from Direct Sunlight: ProClean must be protected from direct sunlight. DO NOT store where container is exposed to direct sunlight.

Shelf life: One year in original unopened container.

Description

ProClean works to reduce buildup and clean and condition metal equipment used in the manufacture of concrete

Recommended For

Cleaning metal equipment

Packaging

5 gallon Pails

55 gallon Drums

265 gallon Totes

Technical Information

Color: Clear Light Yellow

Health & Safety

Consult SDS for Safety Information

Contact

ACM Chemistries, Inc.

P.O. Box 920430 Norcross, GA 30010 770-417-3490 acmchem.com

