


AirFlow™ Spacers

Layer Spacers for Concrete Surface Protection

ColorScape AirFlow Spacers
separate paver layers
allowing air to circulate.



Features and Benefits

- Layer spacers protect concrete surfaces from contact abrasion and scuffing between pallet layers.
- Unique, patent pending shape reduces rolling during dispensing and holds spacers and layers in place during shipping. Spacers will not stack on top of each other, which may cause uneven layers, as can occur with flat shaped spacers.
- High load-bearing capacity.
- Homogeneous pressure transmission.
- More economical than sheet separators and much easier to clean up and dispose of on the jobsite by brushing or vacuuming.
- Reduce cube efflorescence by allowing air to circulate between separated layers and between a top sheet and top layer of units.
- Low Impact - most applications require less than 2 1/2 cups of spacers per pallet.
- ColorScape AirFlow Spacers are manufactured by Green Dot BioPlastics, a leader in BioPlastic manufacturing.

Guidelines for Use

Application: Typical application range is 35 to 70 g per meter² of layer surface area - about 1/6 to 1/3 cup (40 to 80 ml) by volume per layer. Not recommended when pallets are stacked more than 6 levels high. Please consult your Technical Services Representative for more information.



Description

Patent pending, layer spacer
Protects concrete surfaces from contact
abrasion and scuffing between layers

Recommended For

Dry Cast Pavers & Slabs
Wet Cast Pavers & Slabs
Concrete Masonry Units
Segmental Retaining Wall Units

Technical Information

Color: Off-White

Health & Safety

Consult SDS for Health & Safety Information



Airflow™ Spacers

Layer Spacers for Concrete Surface Protection

Recommended Application Method: Dispense manually or through a dedicated automated dispenser. Apply between every layer of units during stacking. If a top sheet is used, include the top layer to provide air flow between the units and the top sheet.

Disposal


Regular waste disposal: ColorScape AirFlow Spacers may be disposed of in regular waste disposal at a jobsite.

Packaging

Gaylord: Available in 2000 lb gaylord containers.

Product Storage and Shelf Life

Storage: ColorScape AirFlow Spacers should be protected from moisture during storage.



Contact

ACM Chemistries, Inc.
P.O. Box 920430 Norcross, GA 30010 770-417-3490 acmchem.com

